

**FM Device connection socket E510**

Order number: 7310063

Type: E510

- With lateral wiring space
- Only 45 mm depth - use in shallow walls

**Dimensions**

Depth	45 - 45 mm
Height	117 mm
Internal depth	43 mm
Length	117 mm
Width	80 mm

**Environmental conditions**

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

**Material**

Socket material	PS
-----------------	----

### Properties

Can be lead sealed	-
Colour	Black
Degree of protection (IP)	IP20
Free of heavy metals	true
Halogen-free	true
Installation type	FM
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

### Technical features

Design voltage	400 V
max. cross section	2,5 mm <sup>2</sup>
Pipe entry M20	2
Pipe entry M20/M25	2
Pipe entry M25	8

### Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"> <li>• DIN EN 60670-1 (VDE 0606-1)</li> <li>• DIN EN 60670-22 (VDE 0606-22)</li> </ul>
VDE	true

### Accessories

Equipped with	None
---------------	------