

### \*Discontinued item\* FM Wall outlet WAD

Order number: 7310077

Type: WAD



All-round success - For easier installation

- Simple exit of cables and pipes in FM areas
- Improved assembly
- For easy installation of wall lights and similar

#### Dimensions

|        |       |
|--------|-------|
| Depth  | 31 mm |
| Height | 60 mm |
| Length | 60 mm |
| Width  | 31 mm |

#### Environmental conditions

|   |        |
|---|--------|
| Ambient temperature (24h)               | 35 °C  |
| Ambient temperature (maximum)           | 40 °C  |
| Ambient temperature (minimum)           | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 %   |
| Max. rel. humidity at 40°C              | 50 %   |

#### Material

|                 |    |
|-----------------|----|
| Socket material | PS |
|-----------------|----|

### Properties

|                           |       |
|---------------------------|-------|
| Can be lead sealed        | -     |
| Colour                    | White |
| Degree of protection (IP) | IP20  |
| Free of heavy metals      | true  |
| Halogen-free              | true  |
| Installation type         | FM    |
| PVC-free                  | true  |
| Silicone-free             | true  |
| Stackable                 | -     |
| Weather-resistant         | -     |

### Technical features

|                    |                     |
|--------------------|---------------------|
| Design voltage     | 400 V               |
| max. cross section | 1,5 mm <sup>2</sup> |
| Pipe entry M16     | 1                   |
| Pipe entry M20     | 3                   |

### Certificates & standards

|                |        |
|----------------|--------|
| CE             | true   |
| Glow wire test | 650 °C |
| REACH          | true   |
| RoHS           | true   |
| VDE            | -      |

### Accessories

|               |      |
|---------------|------|
| Equipped with | None |
|---------------|------|